# Calibration Report: Pressure Transducer

Travis Childrey and Bryan Fabbri
York High / Science Systems and Applications, Inc.
Hampton, Virginia

### Summary

Calibration Date: 18 February 2005 Next Calibration Date: 18 February 2006

A collection, analysis and calibration of data from Vaisala Pressure Transducer, S/N:S4620032 and S/N:S3820006 has been completed. The calibration was performed by the calibration library, Vaisala, Inc. This data was collected by Vaisala, Inc. on February 18, 2005.

MODEL: PTB101B

SERIAL NUMBER: S4620032, S3820006

The test data presented in data table format show the transducers deviation and correction in hPa. The calibration uncertainty is given at 95% confidence level.

Note: Units in hPa per user's request.

APPLICATION: Add corrections to measurements per post calibration table.





### **CALIBRATION CERTIFICATE**

#### after adjustment

Customer

CAMPBELL SCIENTIFIC, INC.

Instrument

PTB101B Analog barometer

Serial number

S3820006

Manufacturer Calibration date Vaisala Oyj, Finland

18th February 2005

Test procedure

doc210609a

This instrument has been calibrated against a Vaisala PTB220 factory working standard which has been calibrated against a Ruska 2465 pressure balance traceable to the National Institute of Standards and Technology (NIST, USA) at Vaisala Measurement Standards Laboratory (MSL). Vaisala MSL has been accredited by the Finish Accreditation System (FINAS) according to ISO/IEC 17025 standard.

At the time of shipment, the instrument described above met its operating specifications.

#### Calibration results

Reference pressure hPa	Observed pressure hPa	Correction* hPa	Uncertainty** hPa
620.2	620.1	0.1	± 0.15
700.2	700.3	-0.1	± 0.15
800.3	800.4	-0.1	± 0.15
850.3	850.4	-0.1	± 0.15
900.3	900.3	0.0	± 0.15
950.3	950.2	0.1	± 0.15
1000.4	1000.4	0.0	± 0.15
1060.2	1060.3	-0.1	± 0.15

<sup>\*</sup>To obtain the true pressure, add the correction to the barometer reading. Interpolated corrections may be used at intermediate readings of the scale of the barometer.

**Equipment used in calibration** 

Certificate number Serial number Calibration date Type Vaisala PTB220 2004-11-16 K008-M01856 X3710015 K008-M01855 Vaisala PTB220 X1260001 2004-11-17 2004-08-02 1000330376 AT 34970A US37047279

Ambient conditions / Humidity 22  $\pm$  5 %RH, Temperature 22  $\pm$  1 °C, Pressure 1007  $\pm$  1 hPa

For Vaisala

Edwige Mehr

This report shall not be reproduced except in full, without the written approval of Vaisala.

doc210635a

<sup>\*\*</sup>The calibration uncertainty given at 95 % confidence level, k = 2



## **CALIBRATION CERTIFICATE**

#### after adjustment

Customer Instrument CAMPBELL SCIENTIFIC, INC.

PTB101B Analog barometer

Serial number

S4620032

Manufacturer Calibration date Vaisala Oyj, Finland 18th February 2005

Test procedure

doc210609a

This instrument has been calibrated against a Vaisala PTB220 factory working standard which has been calibrated against a Ruska 2465 pressure balance traceable to the National Institute of Standards and Technology (NIST, USA) at Vaisala Measurement Standards Laboratory (MSL). Vaisala MSL has been accredited by the Finish Accreditation System (FINAS) according to ISO/IEC 17025 standard.

At the time of shipment, the instrument described above met its operating specifications.

#### Calibration results

Reference pressure hPa	Observed pressure hPa	Correction* hPa	Uncertainty** hPa
620.0	619.7	0.3	± 0.15
700.1	700.1	0.0	± 0.15
800.1	800.1	0.0	± 0.15
850.1	850.0	0.1	± 0.15
900.1	900.0	0.1	± 0.15
950.1	949.9	0.2	± 0.15
1000.1	999.9	0.2	± 0.15
1060.1	1059.9	0.2	± 0.15

<sup>\*</sup>To obtain the true pressure, add the correction to the barometer reading. Interpolated corrections may be used at intermediate readings of the scale of the barometer.

#### Equipment used in calibration

Type	Serial number	Calibration date	Certificate number
Vaisala PTB220	X3710015	2004-11-16	K008-M01856
Vaisala PTB220	X1260001	2004-11-17	K008-M01855
AT 34970A	US37047279	2004-08-02	1000330376

Ambient conditions / Humidity 22 ± 5 %RH, Temperature 22 ± 1 °C, Pressure 1007 ± 1 hPa

Edwige Mehu

This report shall not be reproduced except in full, without the written approval of Vaisala.

doc210635a

<sup>\*\*</sup>The calibration uncertainty given at 95 % confidence level, k = 2